



AZ 16 ZVK-STR

- Long life
- Multiple coding
- Double-insulated
- 52 mm x 90 mm x 30 mm
- Insensitive to soiling
- Thermoplastic enclosure
- Slotted holes for adjustment, circular holes for location
- High level of contact reliability with low voltages and currents

Data

Ordering data

Product type description	AZ 16 ZVK-STR
Article number (order number)	101159958
EAN (European Article Number)	4030661187822
eCl@ss number, Version 9.0	27-27-26-02
eCl@ss number, Version 11.0	27-27-26-02

Approval - Standards

Certificates	TÜV cULus CCC EAC
--------------	----------------------------

General data

Coding level according to ISO 14119	Low
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the contacts, electrical	Silver
Gross weight	120 g

General data - Features

Ejection force	Yes
Number of auxiliary contacts	1
Number of safety contacts	1

Safety appraisal

Standards	BG-GS-ET-15 ISO 13849-1 EN 60947-5-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	2,000,000 Operations
B10d Normally open contact (NO)	1,000,000 Operations
Note (B10d Normally open contact (NO))	at 10% I_e and ohmic load

Mechanical data

Mechanical life, minimum	1,000,000 Operations
positive break travel	8 mm
Positive break force, minimum	10 N
Actuating speed, maximum	2 m/s

Mechanical data - Connection technique

Terminal Connector	Connector plug M12, 4-pole, (A-coding)
--------------------	--

Mechanical data - Dimensions

Length of sensor	30 mm
Width of sensor	52 mm
Height of sensor	90 mm

Ambient conditions

Degree of protection	IP 67 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage U_{imp}	6 kV
---	------

Electrical data

Thermal test current	10 A
Switching element	NO contact, NC contact
Switching principle	Creep circuit element

Electrical data - Safety contacts

Voltage, Utilisation category AC15	230 VAC
------------------------------------	---------

Pictures

Product picture (catalogue individual photo)



ID: kaz16f01


| 471,8 kB | .jpg | 165.806 x 268.817 mm - 470 x 762

Pixel - 72 dpi

| 115,4 kB | .png | 74.083 x 119.944 mm - 210 x 340

Pixel - 72 dpi

Dimensional drawing basic component




ID: kaz16g06

| 176,6 kB | .jpg | 352.425 x 436.386 mm - 999 x 1237

Pixel - 72 dpi

Switch travel diagram




ID: kaz16s01

| 2,0 kB | .png | 74.083 x 25.753 mm - 210 x 73 Pixel -
72 dpi

| 52,0 kB | .jpg | 352.778 x 123.119 mm - 1000 x 349
Pixel - 72 dpi

| 19,8 kB | .cdr |

Diagram



ID: k1o1sk01

| 52,2 kB | .jpg | 352.778 x 143.581 mm - 1000 x 407
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 17/05/2021 05:09:21