



AZ 16 ZVK-STL

- Long life
- Multiple coding
- Double-insulated
- 52 mm x 90 mm x 30 mm
- Insensitive to soiling
- Thermoplastic enclosure
- Slotted holes for adjustment, circular holes for location
- High level of contact reliability with low voltages and currents

Data

Ordering data

Product type description	AZ 16 ZVK-STL
Article number (order number)	101159959
EAN (European Article Number)	4030661187839
eCl@ss number, Version 9.0	27-27-26-02
eCl@ss number, Version 11.0	27-27-26-02

Approval - Standards

Certificates	TÜV
	cULus
	CCC
	EAC

General data

Coding level according to ISO 14119	Low
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the contacts, electrical	Silver
Gross weight	120 g

General data - Features

Ejection force	Yes
Number of auxiliary contacts	1
Number of safety contacts	1

Safety appraisal

Standards	BG-GS-ET-15 ISO 13849-1 EN 60947-5-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	2,000,000 Operations
B10d Normally open contact (NO)	1,000,000 Operations
Note (B10d Normally open contact (NO))	at 10% I_e and ohmic load

Mechanical data

Mechanical life, minimum	1,000,000 Operations
positive break travel	8 mm
Positive break force, minimum	10 N
Actuating speed, maximum	2 m/s

Mechanical data - Connection technique

Terminal Connector	Connector plug M12, 4-pole, (A-coding)
--------------------	--

Mechanical data - Dimensions

Length of sensor	30 mm
Width of sensor	52 mm
Height of sensor	90 mm

Ambient conditions

Degree of protection	IP 67 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage U_{imp}	6 kV
---	------

Electrical data

Thermal test current	10 A
Switching element	NO contact, NC contact
Switching principle	Creep circuit element

Electrical data - Safety contacts

Voltage, Utilisation category AC15	230 VAC
------------------------------------	---------

Current, Utilisation category AC-15	4 A
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	4 A

Electrical data - Auxiliary contacts

Voltage, Utilisation category AC15	230 VAC
Current, Utilisation category AC-15	4 A
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	4 A

Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

Ordering code

Product type description:

AZ 16-(1)ZV(2)K-(3)-(4)-(5)

(1)

without 1 NO contacts/1 NC contact

02 2 NC contact

03 3 NC contact

12 1 NO contact/2 NC contacts

(2)

without Ejection force

R Latching force 30 N

(3)

G24 with LED (only available for version with one NO and one NC contact)

(4)

M16 cable entry M16

M20 Cable entry M20

ST Connector M12, 4 pole, bottom

STL Connector M12, 4 pole, left

STR Connector M12, 4 pole, right

(5)

2254 Latching force 5 N

1762 Front mounting

1637 Gold-plated contacts

Pictures

Product picture (catalogue individual photo)




ID: kaz16f01

| 471,8 kB | .jpg | 165.806 x 268.817 mm - 470 x 762 Pixel - 72 dpi

| 115,4 kB | .png | 74.083 x 119.944 mm - 210 x 340 Pixel - 72 dpi


Dimensional drawing basic component



ID: kaz16g05

| 180,2 kB | .jpg | 352.425 x 436.386 mm - 999 x 1237 Pixel - 72 dpi

Switch travel diagram



ID: kaz16s01

| 2,0 kB | .png | 74.083 x 25.753 mm - 210 x 73 Pixel - 72 dpi

| 52,0 kB | .jpg | 352.778 x 123.119 mm - 1000 x 349 Pixel - 72 dpi

| 19,8 kB | .cdr |

Diagram



ID: k1o1sk01

| 52,2 kB | .jpg | 352.778 x 143.581 mm - 1000 x 407 Pixel - 72 dpi