



AZ17-11ZK-ST

- Long life
- Small body
- Multiple coding
- Double-insulated
- 8 actuating planes
- Insensitive to soiling
- 30 mm x 78.5 mm x 30 mm
- Thermoplastic enclosure
- Connector M12 x 1, 4-pole
- High level of contact reliability with low voltages and currents

Data

Ordering data

Product type description	AZ 17-11ZK-ST
Article number (order number)	101140772
EAN (European Article Number)	4030661119717
eCl@ss number, Version 9.0	27-27-26-02
eCl@ss number, Version 11.0	27-27-26-02

Approval - Standards

Certificates	BG
	cULus
	CCC
	EAC
	CNCA

General data

Product name	AZ 17
Coding level according to ISO 14119	Low
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the contacts, electrical	Silver
Gross weight	85 g

General data - Features

Number of auxiliary contacts	1
------------------------------	---

Number of safety contacts	1
---------------------------	---

Safety appraisal

Standards	EN ISO 13849-1
-----------	----------------

Mission Time	20 Year(s)
--------------	------------

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	2,000,000 Operations
-----------------------------------	----------------------

B10d Normally open contact (NO)	1,000,000 Operations
---------------------------------	----------------------

Note (B10d Normally open contact (NO))	at 10% I_e and ohmic load
--	-----------------------------

Mechanical data

Mechanical life, minimum	1,000,000 Operations
--------------------------	----------------------

Latching force	5 N
----------------	-----

positive break travel	11 mm
-----------------------	-------

Positive break force, minimum	17 N
-------------------------------	------

Actuating speed, maximum	2 m/s
--------------------------	-------

Mechanical data - Connection technique

Terminal Connector	Connector plug M12, 4-pole, (A-coding)
--------------------	--

Mechanical data - Dimensions

Length of sensor	30 mm
------------------	-------

Width of sensor	30 mm
-----------------	-------

Height of sensor	78.5 mm
------------------	---------

Ambient conditions

Degree of protection	IP 67 to IEC/EN 60529
----------------------	-----------------------

Ambient conditions - Insulation value

Rated insulation voltage U_i	250 V
--------------------------------	-------

Rated impulse withstand voltage U_{imp}	4 kV
---	------

Electrical data

Thermal test current	10 A
----------------------	------

Utilisation category AC-15	230 VAC
----------------------------	---------

Utilisation category AC-15	4 A
----------------------------	-----

Utilisation category DC-13	24 VDC
----------------------------	--------

Utilisation category DC-13	4 A
----------------------------	-----

Switching element	NO contact, NC contact
-------------------	------------------------

Switching principle	Creep circuit element
---------------------	-----------------------

Scope of delivery

Included in delivery Actuators must be ordered separately.
Slot cover for dust-proof covering of the opening not in use

Notes

Note (General) Individual coding available on request

Ordering code

Product type description:

AZ 17-(1)Z(2)K-(3)-(4)-(5)

(1)

11 1 NO contacts/1 NC contact

02 2 NC contact

(2)

without Latching force 5 N

R Latching force 30 N

(3)

without M16 cable gland

2243 Front cable entry

2243-1 Rear cable entry

ST M12 connector, 4 pole

(4)

1637 Gold-plated contacts

(5)

5M Cable length 5 m

6M Cable length 6 m

Pictures

Product picture (catalogue individual photo)

Generated on 24/05/2021 04:22:12