

AZ17-02ZI-ST-B5



- Long life
- Small body
- Double-insulated
- Individual coding
- 8 actuating planes
- 30 mm x 60 mm x 30 mm
- Insensitive to soiling
- Thermoplastic enclosure
- Connector M12 x 1, 4-pole
- Slot sealing plug included
- Coding level "High" according to ISO 14119
- Particularly suitable for hinged guards (front mounting)
- High level of contact reliability with low voltages and currents

Data

Ordering data

Product type description	AZ 17-02ZI-ST-B5
Article number (order number)	101144083
EAN (European Article Number)	4030661130828
eCl@ss number, Version 9.0	27-27-26-02
eCl@ss number, Version 11.0	27-27-26-02

Approval - Standards

Certificates	BG cULus EAC
--------------	--------------------

General data

Product name	AZ 17ZI
Coding level according to ISO 14119	High
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the actuator	Stainless steel
Material of the contacts, electrical	Silver
Gross weight	90 g

General data - Features

Number of safety contacts 2

Safety appraisal

Standards EN ISO 13849-1

Mission Time 20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC) 2,000,000 Operations

Mechanical data

Mechanical life, minimum 1,000,000 Operations

Latching force 5 N

positive break travel 11 mm

Positive break force, minimum 17 N

Actuating speed, maximum 2 m/s

Mechanical data - Connection technique

Terminal Connector Connector M12

Mechanical data - Dimensions

Length of sensor 30 mm

Width of sensor 30 mm

Height of sensor 85 mm

Ambient conditions

Degree of protection IP 67 to IEC/EN 60529

Ambient temperature, minimum -30 °C

Ambient temperature, maximum +80 °C

Ambient conditions - Insulation value

Rated insulation voltage U_i 250 V

Rated impulse withstand voltage U_{imp} 4 kV

Electrical data

Operating voltage, maximum 230 V

Thermal test current 10 A

Utilisation category AC-15 230 VAC

Utilisation category AC-15 4 A

Utilisation category DC-13	24 VDC
Utilisation category DC-13	4 A
Switching element	Opener (NC)
Switching principle	Creep circuit element

Scope of delivery

Included in delivery	Not available as spare part Slot cover for dust-proof covering of the opening not in use
Delivery scope of Mounting material	Tamperproof screws

Notes

Note (General)	minimum actuating radius on rotating guard systems via the narrow edge of the actuator 140 mm minimum actuating radius on hinged guards in line with the plane of the actuator 200 mm The axis of the hinge must be 13 mm above and in a parallel plane to the top surface of the safety switch. The actuator is not available separately.
----------------	--

Ordering code

Product type description:

AZ 17-(1)Z(2)I-(3)-(4)-(5)

(1)

11 1 NO contacts/1 NC contact

02 2 NC contact

(2)

without Latching force 5 N

R Latching force 30 N

(3)

without M16 cable gland

ST M12 connector

(4)

B1 Actuator B1


B5 Actuator B5

B6L Actuator B6L

B6R Actuator B6R

(5)


Actuating radius



ID: kaz17r04

| 20,6 kB | .cdr |


Actuating radius



ID: kaz17r03

| 20,6 kB | .cdr |

Dimensional drawing actuator



ID: 1az17b06

| 3,7 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel
- 72 dpi

| 74,6 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697
Pixel - 72 dpi

| 36,2 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 25/05/2021 03:15:00