



SCG01.103

- Long life
- Metal enclosure
- 50 mm x 120 mm x 43 mm
- Head positioned to the front

Data

Ordering data

Product type description	SCG01.103
Article number (order number)	101020914
eCl@ss number, Version 9.0	27-27-26-02
eCl@ss number, Version 11.0	27-27-26-02

Approval - Standards

Certificates	cULus
--------------	-------

General data

Product name	SCG
Standards	EN 60947-5-1 EN ISO 14119 BG-GS-ET-15
Enclosure material	Aluminium
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Gross weight	325 g

General data - Features

Number of auxiliary contacts	1
Number of safety contacts	1

Safety appraisal

Standards	EN ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	2,000,000 Operations
B10d Normally open contact (NO)	1,000,000 Operations

Mechanical data

Mechanical life, minimum	1,000,000 Operations
positive break travel	11 mm
Positive break force, minimum	5 N
Note (Positive break force)	per NC

Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable section, minimum	0.5 mm ²
Cable section, maximum	2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Length of sensor	43 mm
Width of sensor	50 mm
Height of sensor	120 mm

Ambient conditions

Degree of protection	IP 67 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+70 °C

Ambient conditions - Insulation value

Rated insulation voltage U_i	400 V
Rated impulse withstand voltage U_{imp}	2.5 kV

Electrical data

Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	8 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	5 A
Switching element	NO contact, NC contact
Switching principle	Creep circuit element

Scope of delivery

Included in delivery

Actuators must be ordered separately.

Ordering code

Product type description:

SCG(1)/(2)

(1)

01 Head positioned to the front

02 Head positioned to the left

03 Head positioned to the right

04 Head positioned to the rear

(2)

103 1 NC contact / 1 NO contact slow action switching contact

220 2 NC contacts slow action switching contact

92 1 NC contact / 1 NO contact snap switching element

Pictures

Product picture (catalogue individual photo)



ID: kscg-f01


| 89,7 kB | .png | 74.083 x 144.286 mm - 210 x 409

Pixel - 72 dpi

| 1,0 MB | .jpg | 320.675 x 625.122 mm - 909 x 1772

Pixel - 72 dpi

Dimensional drawing basic component



ID: kshg-g02

| 4,0 kB | .png | 74.083 x 48.331 mm - 210 x 137 Pixel
- 72 dpi

| 108,9 kB | .jpg | 352.778 x 229.306 mm - 1000 x 650

Pixel - 72 dpi

| 31,0 kB | .cdr |

Switch travel diagram

ID: kshg-s02




| 19,6 kB | .cdr |

| 1,5 kB | .png | 74.083 x 17.992 mm - 210 x 51 Pixel -
72 dpi

| 33,4 kB | .jpg | 352.778 x 85.019 mm - 1000 x 241
Pixel - 72 dpi

Diagram



ID: ktzg-k01

| 53,1 kB | .jpg | 352.778 x 128.058 mm - 1000 x 363
Pixel - 72 dpi

| 17,6 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 26/05/2021 05:13:37