



SFB-Y-SLCG-8P-S-G-1M-BK-2-X-A-4

- Y-adapter suitable for the series: SLC / SLG 440
- For connecting optoelectronic safety switching devices

Data

Ordering data

Product type description	SFB-Y-SLCG-8P-S-G-1M-BK-2-X-A-4
Article number (order number)	103032867
EAN (European Article Number)	4030661529899
eCl@ss number, Version 9.0	27-44-01-06
eCl@ss number, Version 11.0	27-44-01-06
ETIM number, version 6.0	EC002925
ETIM number, version 7.0	EC002925

General data

Product name	Y-adapter
Connector (electric)	1 x Male connector, 8-pole 1 x Female connector, 8-pole
Gross weight	87.1 g

Mechanical data - Connection technique

Length of cable	1 m
Wire cross-section	0.25 mm ²
Cable diameter	4.3 mm
Bending radius (fixed)	5 x Ø-cable
Bending radius (repeated)	10 x Ø-cable
Colour of the Cable mantle	Black

Mechanical data - connector side A

Connector coding	A
Connector latching	Screw locking

Material of the gland	Metal, CuZn, nickel-plated
Material of the handle	Plastic, TPU

Mechanical data - Dimensions

Length	54.5 mm
Width	33 mm
Height	20 mm
Diameter of the ISO-thread	M12

Ambient conditions

Degree of protection	IP 67 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+75 °C

Electrical data

Thermal test current	2 A
Rated operating voltage	30 V
Operating current	2,000 mA

Accessory

Recommendation (product combination)

Pictures

Product picture (catalogue individual photo)



ID: ksfb-f21

| 185,7 kB | .jpg | 352.778 x 254.353 mm - 1000 x 721

Pixel - 72 dpi

| 22,8 kB | .png | 74.083 x 53.269 mm - 210 x 151

Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 04/05/2021 08:58:35