



EX-RSS16-D-10M-3G/D



- Thermoplastic enclosure
- Door stop with magnetic latching
- 3 different directions of actuation
- Explosion protection for ATEX Zones 2 and 22
- RFID-technology for needs-based protection against tampering

Data

Ordering data

Product type description	EX-RSS16-D-10M-3G/D
Article number (order number)	103027921
EAN (European Article Number)	4030661527512
eCl@ss number, Version 9.0	27-27-24-01

Approval - Standards

Certificates	TÜV
--------------	-----

General data

Housing construction form	Block
Gross weight	0.5 g

Mechanical data

Active area	lateral front side cover-side
Switch distance	15 mm
Ensured switch distance "ON" S_{ao}	12 mm
Ensured switch distance "OFF" S_{ar}	30 mm

Ambient conditions

Degree of protection	IP 65 to IEC/EN 60529 IP 67 to IEC/EN 60529
----------------------	--

Accessory

Recommendation (actuator)	RST16-1
Recommended safety switchgear	PROTECT PSC1
	SRB-E-301ST
	SRB-E-201LC

Ordering code

Product type description:
EX-RSS16-(1)(2)(3)(4)-3GD

(1)

without Standard coding

I1 Individual coding

I2 Individual coding, for multiple applications

(2)

D With diagnostic output

SD With serial diagnostic function

(3)

without without latching

R With latching, latching force 40 ... 60 N

(4)

without Connecting cable, Cable length 10 m

Pictures

Product picture (catalogue individual photo)



ID: kxrs1f05

| 440,6 kB | .jpg | 352.778 x 528.814 mm - 1000 x 1499 Pixel - 72 dpi

| 30,9 kB | .png | 73.731 x 110.772 mm - 209 x 314 Pixel - 72 dpi

Dimensional drawing basic component

