



EX-RSS16-I2-D-10M-3G/D



- Thermoplastic enclosure
- 3 different directions of actuation
- Explosion protection for ATEX Zones 2 and 22
- RFID-technology for needs-based protection against tampering

Data

Ordering data

Product type description	EX-RSS16-I2-D-10M-3G/D
Article number (order number)	103034308
EAN (European Article Number)	4030661535258
eCl@ss number, Version 9.0	27-27-24-01

Approval - Standards

Certificates	TÜV
--------------	-----

General data

Gross weight	594.5 g
--------------	---------

Accessory

Recommendation (actuator)	RST16-1
	PROTECT PSC1
Recommended safety switchgear	SRB-E-301ST
	SRB-E-201LC

Ordering code

Product type description:
EX-RSS16-(1)(2)(3)(4)-3GD

(1)

without Standard coding

I1 Individual coding

I2 Individual coding, for multiple applications

(2)

D With diagnostic output

SD With serial diagnostic function

(3)

without without latching

R With latching, latching force 40 ... 60 N

(4)

without Connecting cable, Cable length 10 m

Pictures

Product picture (catalogue individual photo)




ID: kxrs1f05

| 440,6 kB | .jpg | 352.778 x 528.814 mm - 1000 x 1499 Pixel - 72 dpi

| 30,9 kB | .png | 73.731 x 110.772 mm - 209 x 314 Pixel - 72 dpi

Dimensional drawing basic component




ID: krss1g02

| 4,7 kB | .png | 74.083 x 57.503 mm - 210 x 163 Pixel - 72 dpi

| 132,3 kB | .jpg | 352.778 x 273.403 mm - 1000 x 775 Pixel - 72 dpi

Wiring example



ID: krss1lx2

| 3,9 kB | .png | 74.083 x 56.092 mm - 210 x 159 Pixel - 72 dpi

| 3,0 kB | .jpg | 35.278 x 35.278 mm - 100 x 100 Pixel - 72 dpi

| 117,7 kB | .jpg | 352.778 x 267.053 mm - 1000 x 757 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 07/05/2021 04:06:17